

Kimberley Sandstone

Stone Protection

Stone Pre Seal

Pre Seal is a water-based sealer designed for application to pavers and porous tiles prior to laying to enable easy grout and dirt removal.

Pre Seal dries to an invisible finish that stops water penetration and will help prevent picture framing, efflorescence and mould build up from occurring.

Pre Seal should be applied a minimum of 24 hours before the pavers or tiles are to be used, to allow the sealing process to cure and give the desired water repellent effect.

Application –

Pre Seal can be sprayed, brushed or rolled onto pavers or absorbent tiles

- Surface to be treated should be dry and absorbent
- Completely wet the surface with **Pre Seal**
- Wait for several minutes to allow penetration
- Wipe off any excess
- One coat would be sufficient
- **One litre will cover 10-12 sq metres approx dependant on stone porosity.**
- Available in 5,10Litre, 20Litre Drums

After pre-sealing it is highly recommended that you use Stone guard.

Stone Guard – “Maximum” stain resistance properties of any Elite natural looking penetrating sealers. It protects porous surfaces from both water and oil based contaminants such as salt, mould, mildew, tea, coffee, wine and graffiti. It also assists in the easier removal of chewing gum.

Please Note:

This data sheet is to provide information on the product based on current knowledge. It does not constitute a guarantee and we recommend that testing should be undertaken to ensure that the final result is satisfactory for the intended application. The quality of the product is guaranteed under our General Conditions of Sale.

Email: kimberleysandstone@bigpond.com or phone 0400 458 399

**STONE Pre-Seal. Price List 2013, includes delivery – 5Litre \$145+gst
10Litre \$220+gst
20Litre \$340+gst**